

Appl. No. 10/650,267

Amdt. Dated September 22, 2006

Reply to Office Action of July 5, 2006

RECEIVED
CENTRAL FAX CENTER

SEP 22 2006

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the above-identified application:

1. (currently amended): An energy storage flywheel system, comprising:
a housing assembly;

a flywheel assembly rotationally mounted in the housing assembly;

one or more magnetic bearing assemblies mounted in the housing assembly, each magnetic bearing assembly adapted to be selectively activated and deactivated, and configured, when activated, to rotationally mount the flywheel assembly in non-contact manner, wherein each actuator assembly is configured to engage the flywheel assembly, and disengage the flywheel assembly; and

one or more actuator assemblies mounted in the housing assembly, each actuator assembly configured to selectively (i) engage the flywheel assembly, to thereby inhibit at least rotational movement thereof when each of the magnetic bearing assemblies is deactivated, and (ii) disengage the flywheel assembly, to thereby allow at least rotational movement thereof when each of the magnetic bearing assemblies is activated.

2. (original): The system of Claim 1, further comprising:

a control circuit configured to selectively supply an engage signal and a disengage signal,

wherein each actuator assembly is coupled to receive the engage and disengage signals from the control circuit and operable, in response thereto, to engage and disengage the flywheel assembly, respectively.

3. (canceled).

Appl. No. 10/650,267

Amdt. Dated September 22, 2006

Reply to Office Action of July 5, 2006

4. (currently amended): The system of Claim [[3]] 1, further comprising:
a control circuit configured to selectively supply an engage signal when the magnetic bearing assembly is deactivated, and a disengage signal when the magnetic bearing assembly is activated,

wherein each actuator assembly is coupled to receive the engage and disengage signals from the control circuit and operable, in response thereto, to engage and disengage the flywheel assembly, respectively.

5. (original): The system of Claim 4, wherein each actuator assembly comprises:
a solenoid coupled to receive the engage and disengage signals from the actuator assembly control circuit and operable, in response thereto, to move in an engage and disengage direction, respectively; and

an actuator coupled to the solenoid and configured to (i) engage the flywheel assembly when the solenoid moves in the engage direction and (ii) disengage the flywheel assembly when the solenoid moves in the disengage direction.

6. (original): The system of Claim 5, wherein each solenoid is a latch-type solenoid.

7. (currently amended): The system of Claim [[3]] 1, further comprising:
one or more mechanical bearing assemblies mounted in the housing assembly, each mechanical bearing assembly coupled to the flywheel assembly and configured to rotationally mount the flywheel assembly at least when each of the magnetic bearing assemblies is deactivated.

8. (currently amended): The system of Claim [[3]] 1, further comprising:
a magnetic bearing control circuit adapted to receive bearing command signals and operable, in response thereto, to supply at least the activation and deactivation signals to each of the magnetic bearings.

Appl. No. 10/650,267

Amdt. Dated September 22, 2006

Reply to Office Action of July 5, 2006

9. (original): The system of Claim 1, wherein the flywheel assembly comprises:
a shaft;
a flywheel hub coupled to and surrounding the shaft; and
a flywheel coupled to and surrounding the flywheel hub,
wherein each actuator assembly is configured to selectively engage and disengage
the flywheel hub.

10. (original): The system of Claim 1, wherein each actuator assembly, when
engaging the flywheel assembly, inhibits both rotational movement and translational
movement of the flywheel assembly.

11. (currently amended): An energy storage flywheel system, comprising:
a housing assembly;
a flywheel assembly rotationally mounted in the housing assembly;
one or more magnetic bearing assemblies mounted in the housing assembly, each
magnetic bearing assembly adapted to receive (i) an activation command, whereby the
magnetic bearing assembly rotationally mounts the flywheel assembly in non-contact
manner or (ii) an inactivation command, whereby the magnetic bearing assembly does not
rotationally mount the flywheel assembly;

one or more actuator assemblies mounted in the housing assembly, each actuator
assembly adapted to receive (i) an engage signal, whereby the actuator engages the
flywheel assembly at least against rotational movement or (ii) a disengage signal,
whereby the actuator disengages the flywheel assembly; and

an actuator assembly control circuit configured to (i) supply the engage signal to
each actuator assembly at least when the inactivation command is supplied to the
magnetic bearing assembly and (ii) supply the disengage signal to each actuator assembly
at least when the activation command is supplied to the magnetic bearing assembly.

12. (original): The system of Claim 11, further comprising:

Appl. No. 10/650,267

Amdt. Dated September 22, 2006

Reply to Office Action of July 5, 2006

a magnetic bearing controller adapted to receive bearing command signals and operable, in response thereto, to supply at least the activation and deactivation signals to each of the magnetic bearings.

13. (currently amended): The system of Claim ~~[[1]]~~ 11, wherein each actuator assembly comprises:

a solenoid coupled to receive the engage and disengage signals from the actuator assembly control circuit and operable, in response thereto, to move in an engage and disengage direction, respectively; and

a lock mechanism coupled to the solenoid and configured to (i) engage the flywheel assembly when the solenoid moves in the engage direction and (ii) disengage the flywheel assembly when the solenoid moves in the disengage direction.

14. (currently amended): The system of Claim 13, wherein each solenoid is a latch~~[[type]]~~ solenoid.

15. (original): The system of Claim 11, further comprising:

one or more mechanical bearing assemblies mounted in the housing assembly, each mechanical bearing assembly coupled to the flywheel assembly and configured to rotationally mount the flywheel assembly at least when each of the magnetic bearing assemblies is deactivated.

16. (original): The system of Claim 11, wherein the flywheel assembly comprises:

a shaft;

a flywheel hub coupled to and surrounding the shaft; and

a flywheel coupled to and surrounding the flywheel hub,

wherein each actuator assembly is configured to selectively engage and disengage the flywheel hub.

Appl. No. 10/650,267

Amdt. Dated September 22, 2006

Reply to Office Action of July 5, 2006

17. (original): The system of Claim 11, wherein each actuator assembly, when engaging the flywheel assembly, inhibits both rotational movement and translational movement of the flywheel assembly.

18. (currently amended): A method of selectively inhibiting rotation of a rotationally mounted flywheel assembly, wherein the flywheel assembly is rotationally mounted using one or more magnetic bearing assemblies that are each adapted to be selectively activated and deactivated, and configured, when activated, to rotationally mount the flywheel assembly in non-contact manner, the method comprising the steps of:

engaging at least a portion of the flywheel assembly at least when each of the magnetic bearing assemblies is deactivated, to thereby substantially inhibit at least flywheel assembly rotational movement; and

disengaging the flywheel assembly at least when each of the magnetic bearing assemblies is activated, to thereby allow at least flywheel assembly rotational movement.

19. (canceled).

20. (original): The method of Claim 18, wherein the flywheel assembly movement that is substantially inhibited and allowed includes both rotational movement and translational movement.